



**Specifications Philips LED Panel**  
**CoreLine RC132V 33,5W 3600lm - 840**  
**Cool White | 60x60cm - UGR <22 -**  
**Interact Dimmable - Emergency 3H**

[View Product](#)

## General Information

|                          |                                          |
|--------------------------|------------------------------------------|
| SKU                      | 246350                                   |
| EAN                      | 8720169013902                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | RC132V G5 36S/840 WIA W60L60 NOC ELB3 W4 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |
| Series                   | RC132V                                   |

## Technical Information

|                             |                                |
|-----------------------------|--------------------------------|
| Technology                  | LED Integrated                 |
| Voltage (V)                 | 220-240                        |
| Dimmable                    | Dimmable with Philips Interact |
| Colour Code                 | 840 Cool White                 |
| Colour temperature (Kelvin) | 4000 Cool White                |
| Colour Rendering (Ra)       | 80-89                          |
| Colour of Light             | White                          |
| Light colour options        | Single Color                   |
| Including bulb              | Yes                            |
| Amount of bulbs required    | 1                              |
| Luminous Efficacy (lm/W)    | 107                            |

|                        |                               |
|------------------------|-------------------------------|
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Fixture Connection     | PI [Push-in connector 4-pole] |
| Finish of Reflector    | Acrylate                      |
| Power factor           | >0.90                         |
| Product Type Category  | LED Panel                     |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| EOC8                  | 01390200                 |
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | 0 to +35                 |
| Emergency Lighting    | 3H Emergency Light       |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |
| Colour of material    | White                    |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 70      |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process